




The Easy-Lock™ Standing Seam is the only metal roofing panel with a patented no-siphon dry lock seam, with a unique reversing feature to allow installation of panels from both directions starting at any location. The panel is designed with softer, less industrial lines to provide an architecturally pleasing appearance.




- Prevents crowning
- No visible screws required
- Sharp, professional appearance

KEY FEATURES


- 12", 16" and 18" coverage options
- 26, 24 & 22 gauge Tru-Gauge™, .032 Aluminum and 24 gauge Bonderized (G-90)
- 16 & 20 oz. Copper *please inquire*
- Factory-notched panels available
- Vertical interlocking application: allows installation from both directions starting at any location
- Patented no-siphon lock seam
- 1 1/8" vertical rib with 3/8" flat top for ease of flashing attachment
- Concealed fasteners: fasteners cannot leak
- Pre-slotted fastener flange: allows expansion/contraction of panel
-  - Code compliance UL Evaluation Report UL ER 25913-01
- UL580 Class 90 wind uplift, UL Class A fire rated
- UL Construction No. 529
- 3:12 minimum pitch recommended: for lower pitches please inquire
- Standard panel lengths 2' to 35': for longer panels, please inquire
- Pan options: Flat pan, Accent ribs, Striations

PANEL PROFILES




FLAT PAN

12", 16" and 18" coverage options




ACCENT RIBS

3 Accent ribs for 12" panel
4 Accent ribs for 16" & 18" panel




STRIATED

LOCK SEAM DETAIL



REVERSE LAP DETAIL




MATERIAL SPECIFICATIONS

- 26 gauge Kynar 500® Painted Steel
.019" (thickness prior to painting)
G-90 Galvanized or AZ-50
- 24 gauge Kynar 500® Painted Steel
.0236" (thickness prior to painting)
G-90 Galvanized or AZ-50
- 24 & 22 gauge bare Zincolume® Plus with Clear Acrylic Coating-AZ-55
- ▲ 22 gauge Kynar 500® Painted Steel
.029" (thickness prior to painting)
G-90 Galvanized or AZ-50
- ♦ .032 Kynar 500® Painted Aluminum
- 22 gauge Rusteel™ (cold-rolled)
- 22 gauge Rusteel Plus™ (A606)
- 24 gauge Bonderized (G-90)
- 16 and 20 ounce Copper *please inquire*
- Kynar and substrate testing data available
(See website)


KEY FEATURES

- 21 Standard Colors, 5 Metallic Colors and 5 Specialized Colors
- Kynar 500® Paint System-the ultimate in exterior durability and color retention
- "Cool" color pigments are specially designed to reflect infrared light, reducing heat gain to dwelling, and conform with ENERGY STAR® criteria
- Superior quality, two-coat, 70% resin finish, applied at a 1 mil. thickness
- 40-year residential paint warranty
- 20 and 30 year commercial paint warranty:
(Contact TMP for warranty specifications)




40-Year Residential/ 20 and 30 Year Commercial Manufacturer's Limited Warranty

STANDARD 24g COOL KYNAR 500® COLORS




METALLIC COOL KYNAR 500® COLORS



These printed chips provide a close representation of the colors.
Metal samples are available upon request.
Coatings are low gloss 10-15% sheen

Oil Canning is an inherent characteristic of Roof & Wall products, not a defect, and is not a cause for panel rejection. SRI = Solar Reflective Index. SRI values listed above are in accordance with ASTM E 1980 and are based on actual testing.

SPECIALIZED MATERIAL



Standard Panels				
Width	Gauge	Color	LBS SQFT	LBS LF
12"	26	1	1.13	1.13
12"	24	2	1.33	1.33
16"	24	3	1.24	1.65
18"	24	4	1.21	1.82
16"	.032	♦	.58	.78
16"	22	▲	2.07	2.75



steelscape



(Inquire for other panel sizes)